



Plan View
Scale: 1" = 20'

Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Beyond Site	+	0.0 fc	1.0 fc	0.0 fc	N/A	N/A
Parking Lot	+	1.9 fc	13.2 fc	0.6 fc	22.0:1	3.2:1
Property Line	+	0.3 fc	1.7 fc	0.0 fc	N/A	N/A
Site	+	1.3 fc	12.8 fc	0.0 fc	N/A	N/A

Symbol	Label	Image	QTY	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Filename	Lumens per Lamp	Lumen Multiple	LLF	Wattage	Efficiency	Distrib	Polar Plot	MOUNTING HEIGHT	Notes
	S1		3	Lithonia Lighting	KAD LED 40C 700 40K R4 MVOLT HS	KAD LED, 40 LED, 700mA MVOLT DRIVER, 4000K, TYPE 4 OPTICS WITH HOUSE SIDE SHIELDS		1	KAD_LED_40C_700_40K_R4_M_VOLT_HS.ies	8619	1	0.9	94	100%	TYPE III, SHORT, BUC RATING: B1 - U0 - G2		23'-6"	
	S2		3	Lithonia Lighting	KAD LED 40C 700 40K R4 MVOLT	KAD LED, 40 LED, 700mA MVOLT DRIVER, 4000K, TYPE 4 OPTICS.		1	KAD_LED_40C_700_40K_R4_M_VOLT.ies	11012	1	0.9	188	100%	TYPE IV, MEDIUM, BUC RATING: B2 - U0 - G2		23'-6"	
	WP		14	Lithonia Lighting	WST LED P2 40K VF MVOLT	WST LED, Performance package 2, 4000 K, visual comfort forward throw, MVOLT	LED	1	WST_LED_P2_40K_VF_MVOLT.ies	3469	1	0.9	25	100%	TYPE III, VERY SHORT, BUC RATING: B1 - U0 - G1		10'-0"	
	WP2		3	Lithonia Lighting	WST LED P2 40K VW MVOLT	WST LED, Performance package 2, 4000 K, visual comfort wide, MVOLT	LED	1	WST_LED_P2_40K_VW_MVOLT.ies	3511	1	0.9	25	100%	TYPE II, VERY SHORT, BUC RATING: B1 - U0 - G0		10'-0"	
	WP3		1	Lithonia Lighting	WST LED P3 40K VF MVOLT	WST LED, Performance package 3, 4000 K, visual comfort forward throw, MVOLT	LED	1	WST_LED_P3_40K_VF_MVOLT.ies	6609	1	0.9	50	100%	TYPE III, VERY SHORT, BUC RATING: B1 - U0 - G1		10'-0"	

Designer
KJK
DMT
Date
04/14/2021
Scale
Not to Scale
Drawing No.
LC100
Summary